

ISD15

INDUSTRIAL SMART DISPLAY

The slim-profile, lightweight ISD15 all-in-one computer display offers a robust combination of technology including a powerful Intel processor, Windows Operating System, high contrast LCD, touch-screen interface, integrated speaker, Gigabit Ethernet connection, and USB connectivity in a sealed billet aluminum enclosure. The low power rugged ISD15 is an ideal solution for harsh applications in need of a smart network display.

STANDARD FEATURES

- Intel Celeron® Processor
- Intel HD Graphics
- 8GB System Memory
- mSATA Storage
- Windows® OS Support
- 15.0" LCD, XGA Resolution (1024 x 768)
- Resistive Touch Screen
- LED Backlight
- High Contrast Ratio (1500:1)
- Integrated Sealed Speaker
- Gigabit Ethernet
- USB 2.0
- 120VAC Power Input
- IP65 Sealed Enclosure
- VESA Mount (75mm) Compatible
- Hard Anodized Finish
- Auto-ON





LCD SPECIFICATIONS				
LCD SIZE	RESOLUTION	BRIGHTNESS	VIEWING ANGLE	CONTRAST RATIO
15.0" TFT AM LCD	XGA (1024 x 768)	300 nits	170° (H) x 170° (V)	1500:1

PROCESSOR SPECIFICATIONS					
CPU	SPEED	MEMORY	STORAGE	GRAPHICS	CACHE
Intel Celeron®	2GHz - 2.42GHz	DDR3L, 8GB	128GB mSATA	Intel HD Graphics	2MB

SYSTEM SPECIFICATIONS					
DISPLAY	ENCLOSURE	MOUNTING	AC POWER INPUT	OPERATING TEMPERATURE	STORAGE TEMPERATURE
8-bit color, 16.7 million colors	Milled Aluminum, Gray Anodized	VESA 75mm	120V	0°C to +55°C	-20°C to +70°C

IP RATING	HUMIDITY
IP65	0-95%

ON-GOING PRODUCT DEVELOPMENT MAY NECESSITATE DESIGN AND SPECIFICATION CHANGES WITHOUT NOTICE.